

# C-Infra

Installation Series



## System data

Frequency response (-5 dB standard)	25Hz -125Hz
Max. sound pressure (1 m, free field)	139 dB SPL

## Loudspeaker data

Nominal impedance	8 ohms
Power handling capacity LF (RMS)	1500 W
Components	1 x21" driver with ferrite magnet

## Dimensions, weight

Dimensions (H x W x D)	756 x 586 x 750 mm 29.7 x 23 x 29.5"
Weight	67 kg 146 lb
Finish	Fir-green RAL 6009® Polyurea coating
Cabinet	Baltic birch plywood
Protection Rating:	IP 44

## Amplifiers

Nominal LF Amplifier Power	1x 2000 W @ 4Ω
Nominal Processed Satellite Amplifier Power (CIWI and CIMI series)	1x 800 W @ 4Ω
Connectors	Analog or Digital input Input: Female XLR Loop Thru: Male XLR AC Input: powerCON AC Output: powerCON Remote: rj45 IN/OUT
DSP	Share 300mHz 96KHz sample rate
Delay	200 ms
Presets	24 presets
Max input voltage	5 Vrms/+16 dBu (15K impedente)
Software control	APNET Network Manager
AC Requirements	Universal mains 85-264Vac
Current Draw (1/8 power @ 230 V)	1.8A