

# C-Sub

Installation Series



## System data

Frequency response (-5 dB standard)	45Hz -150Hz
Max. sound pressure (1m, free field)	124 dB SPL

## Loudspeaker data

Nominal impedance	8 ohms
Power handling capacity LF (RMS)	300 W
Components	1x12" driver with ferite magnet

## Dimensions, weight

Dimensions (H x W x D)	356 x 350 x 510 mm	14 x 13.7 x 19.6"
Weight	18.5 kg	40 lb
Finish	Fir-green RAL 6009® Polyurea coating	
Cabinet	Baltic birch plywood	
Rigging	Optional UBRK-8 bracket accessory	
Protection Rating:	IP 44	

## Amplifiers

Nominal LF Amplifier Power	400 W @ 8Ω
Nominal Processed Satallite Amplifier Power (CIWI and CIMI series)	800 W @ 4Ω
Connectors	Analog or Digital input
	Input: Female XLR
	Loop Thru: Male XLR
	AC Input: powerCON
	AC Output: powerCON
	Remote: rj45 IN/OUT
DSP	Share 300mHz 96KHz sample rate
Delay	200 ms
Presets	24 presets
Max input voltage	5 Vrms/+16 dBu (15K impedente)
Software control	APNET Network Manager
AC Requirements	Universal mains 85-264Vac
Current Draw (1/8 power @ 230 V)	1.8A